

**TVT**

**Secure The World With You**

[www.tvt.net.cn](http://www.tvt.net.cn)



# TD-9525S1

**2 MP Network IR Water-proof  
Dome Camera**

**TVT**

TVT DIGITAL TECHNOLOGY CO., LTD.

Address: 5F, North Block, CE Lighting House, Hi-Tech Park, Nanshan District, Shenzhen, Guangdong Province, P.R.China 518057


Tel: +86-755-3330 6001

Fax: +86-755-3330 6002

Web site: [www.tvt.net.cn](http://www.tvt.net.cn)

E-mail: [overseas@tvt.net.cn](mailto:overseas@tvt.net.cn)


## 2 MP Network IR Water-proof Dome Camera



## Features

- 2MP ( 1920 x 1080 ) full real time coding
- Max. resolution: 1920 x 1080
- ICR auto switch, true day / night
- 20 ~ 30m IR night view distance
- Third generation of dot matrix LED IR lights, small size, efficient heat dissipation, long lifespan
- 3D DNR, digital WDR
- ROI coding
- PoE power supply
- Support smart phone, iPad, remote monitoring
- Support P2P
- IP66 ingress protection
- Support three streams

## Dimensions



## Available Accessories



TD-YXH0201



TD-YZJ0802



TD-YZJ0402

## Specifications

Specifications	Model	TD-9525S1
<b>Camera</b>		
Image Sensor		1 / 2.8 "CMOS
Image Size		1920 x 1080
Electronic Shutter		1 / 25 s ~ 1 / 100000 s
Auto Iris		Fixed Iris
Min. Illumination		0.1 lux @F1.2,AGC ON; 0 lux with IR
Lens		2.8 ~ 12 mm @F1.4, angle of view : 96° ~ 35°
Lens Mount		Φ14
Day & Night		ICR
Wide Dynamic Range		Digital WDR
Digital NR		3D DNR
Angle Adjustment		Pan : 0°~360°, Tilt : 0°~90°, Rotation : 0°~360°
<b>Image</b>		
Video Compression		H.264 / MJPEG
H.264 Compression Standard		Baseline Profile / Main Profile / High Profile
Resolution		1080P ( 1920 × 1080 ), 720P ( 1280 × 720 ), D1, CIF, 480 x 240
Main Stream		60Hz : 1080P ( 1 ~ 30fps ) / 720P ( 1 ~ 30fps ) 50Hz : 1080P ( 1 ~ 25fps ) / 720P ( 1 ~ 25fps )
Bit Rate		256Kbps ~ 5Mbps
Encode Mode		VBR / CBR
Quality		Five levels under VBR; Freely adjustable under CBR
Image Settings		ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc. adjustable through client software or web browser
ROI		3 ROI
<b>Interfaces</b>		
Network		RJ45
<b>Functions</b>		
Remote Monitoring		IE browsing, CMS remote control
Online Connection		Support simultaneous monitoring for up to 3 users; Support multi-stream real time transmission
Network Protocol		TCP / IP, UDP, DHCP, NTP, RTSP, DDNS, SMTP, FTP
Interface Protocol		ONVIF
Storage		Network remote storage
Smart Alarm		Motion alarm
PoE		Yes
IR Distance		20 ~ 30 m
Water-proof		IP66
<b>Others</b>		
Power Supply		DC12V / PoE
Power Consumption		< 2.5W
IR Consumption ON		< 5W
Operating Environment		- 40 °C ~ 50 °C, 10 % ~ 90 % humidity
Dimensions ( mm )		Φ109 x 130
Weight ( net )		695g
Installation		Pendent mounting ( Wall mounting available with the junction box and bracket )

## Available Model

Available Model	TD-9525S1 ( D / FZ / PE / AR2 )
-----------------	---------------------------------